



Video dimostrativo
Demonstration movie

FUEGO



FUEGO il nuovo termoventilatore di JOHNSON con resistenza in ceramica a basso consumo.

Grazie ai suoi 2000 W riscalda ambienti abbastanza ampi, ideale per camere, bagni e uffici.

È integra di maglia per il trasporto, ha l'oscillazione automatica selezionabile, 2 temperature con termostato regolabile tiepido e caldo più la ventilazione.

Ha una spia luminosa che ti consente di capire quando il dispositivo è acceso, il filtro posteriore removibile e lavabile per una facile pulizia e ha un sistema di sicurezza auto spegnimento in caso di ribaltamento.

FUEGO puoi posizionarlo in qualunque luogo tu voglia grazie al suo design moderno e compatto.



FUEGO the new JOHNSON fan heater with low consumption ceramic resistance.

Thanks to its 2000 W it heats quite large rooms, ideal for bedrooms, bathrooms and offices.

It is complete with mesh for transport, has selectable automatic oscillation, 2 temperatures with adjustable warm and warm thermostat plus ventilation.

It has an indicator light that allows you to understand when the device is on, the removable and washable rear filter for easy cleaning and has an auto shut-off safety system in case of rollover.

FUEGO you can place it wherever you want thanks to its modern and compact design.



8 008523 012861

GIFT BOX		MASTER CARTON			PALLET	CONTAINER		
Size (mm)	Kg	Size (mm)	Pcs	Kg	Pcs	20	40	40HQ
210 x 170 x 435	2.5		4			1740	3670	4315



SCHEMA PRODOTTO PRODUCT DETAILS

FUEGO

FAMILY	HEATING
CODE	FUE
COD. EAN	8008523012861
COD. ITF	

CARATTERISTICHE	FEATURES
Potenza 1200/2000 W Resistenze in ceramica Basso consumo energetico Oscillazione automatica selezionabile 2 temperature Ventilazione Aria tiepida: 1200 W Aria calda: 2000 W Termostato regolabile Spia luminosa Maniglia integrata Sistema di sicurezza auto spegnimento in caso di ribaltamento dell'apparecchio Sistema di sicurezza anti surriscaldamento Filtro posteriore removibile e lavabile Colore: Bianco/Grigio Alimentazione 220 - 240V~ 50 Hz	Power 1200/2000 W Ceramic resistors Low energy consumption Selectable automatic swing 2 temperatures Ventilation Warm air: 1200 W Hot air: 2000 W Adjustable thermostat Warning light Integrated handle Auto shut-off safety system in case of overturning of the device Overheating safety system Removable and washable rear filter Color: White / Gray Power supply 220 - 240V ~ 50 Hz
Dimensioni prodotto: 195 x 145 x 420 mm Dimensioni imballo: 210 x 170 x 435 mm Peso imballo + prodotto: 2.5 Kg Pezzi per master: 4 pz Dimensioni master: — x — x — mm Peso master: — Kg Pezzi per pallet: — pz Colli per strato: — Strati: — Altezza pallet: — cm Peso pallet: — Kg Container 20: 1740 pz Container 40: 3670 pz Container 40HQ: 4315 pz Codice certificazione: NSBK-200SK35	Product dimensions: 195 x 145 x 420 mm Package dimensions: 210 x 170 x 435 mm Packaging weight + product: 2.5 Kg Master pieces: 4 pcs Master size: — x — x — mm Master Weight: — Kg Pieces for pallet: — pcs Master for layer: — Layers: — Height pallet: — cm Weight pallet: — Kg Container 20: — pcs Container 40: — pcs Container 40HQ: — pcs Certification Code: NSBK-200SK35

